

CAT5e 

Cat5e Riser Unshielded

SKU: RCT-C5ER-BC-BL

24AWG • 4 Twisted Pairs • CMR

U/UTP • 350MHz • Solid Bare Copper

**Lengths Available**

• 1000ft

Jacket Colors

Key Features

- Bandwidth tested up to 350 MHz
- Suitable for 1 Gigabit and 2.5 Gigabit Ethernet up to 328 ft
- In compliance with ANSI/TIA 568.2-D
- RoHS-3 Compliant
- Easily identified color striped pairs
- Supports Power over Ethernet: PoE/PoE+/ PoE++ (IEEE 802.3af/at/bt) 4PPoE up to 100 W
- Sequential footage markings every 2ft

Technical Data

Insulation**PE**

Average Thickness (mm) 0.205

Min Point Thickness (mm) 0.198

Conductor Insulation Dia. (±0.02mm) 0.86

Twisted Pair Dia. (±0.02mm) 1.72

Ripcord Nylon

Spline Not Present

Polyethylene Tape Not Present

Shielding U/UTP

Conductor**Solid Bare Copper**

Size 24AWG

Conductor Dia. (±0.05mm) 0.46

Color of Pairs

Pair 1 Blue- White/Blue

Pair 2 Orange- White/Orange

Pair 3 Green- White/Green

Pair 4 Brown- White/Brown

Cable Jacket**PVC**


Average Thickness (mm) 0.50

Min. Point Thickness (mm) 0.45

Outer Diameter (±0.2mm) 4.60**Standards Reference****ANSI/TIA
568-2.D****ISO/IEC
11801**

Conductor

Insulation



Jacket

Ripcord

Twisted Pairs



CAT5e



Cable ID: 225-C UTP4 CAT5 Riser UTP

Test Limit: TIA Cat 5 Riser Perm. Link

Limits Version: V7.5 Date / Time:

07/09/2021 01:14:46 PM

Operator: LIXIAOHONG

Headroom: 3.5 dB (NEXT 1,2,3,6)

Cable Type: Cat 5 Riser U/UTP NVP:

69.0%

Main: Versiv

S/N: 2034142

Software Version: V6.5 Build 5

Calibration Date: 12/23/2020

Adapter: DSX-8000 (DSX-PLA804)

S/N: 20475125

Test Summary: PASS

Remote: Versiv

S/N: 2035009

Software Version: V6.5 Build 5

Calibration Date: 12/23/2020

Adapter: DSX-8000R (DSX-PLA804)

S/N: 20485133

Length (ft), Limit 295	[Pair 3,6]	305
Prop. Delay (ns), Limit 498	[Pair 7,8]	464
Delay Skew (ns), Limit 44	[Pair 7,8]	15
Resistance (ohms)	[Pair 7,8]	15.53
Insertion Loss Margin (dB)	[Pair 7,8]	1.6
Frequency (MHz)	[Pair 7,8]	250.0
Limit (dB)	[Pair 7,8]	31.1

Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	3.6-4.5	1.2-3.6	3.6-4.5	1.2-4.5
NEXT (dB)	3.9	3.5	6.0	5.5
Freq. (MHz)	35.5	80.8	246.0	210.5
Limit (dB)	49.1	43.3	35.5	36.6
Worst Pair	3.6	3.6	3.6	4.2
PS NEXT (dB)	5.2	4.4	6.2	6.0
Freq. (MHz)	59.6	40.6	33.1	33.6
Limit (dB)				


PASS	MAIN	SR	MAIN	SR
Worst Pair	3.6-1.2	3.6-1.2	3.6-1.2	3.6-1.2
ACR-F (dB)	2.0	1.8	2.0	1.9
Freq. (MHz)	209.5	151.0	209.5	208.5
Limit (dB)	17.8	20.6	17.8	17.8
Worst Pair	1.2	1.2	1.2	1.2
PS ACR-F (dB)	4.3	4.3	4.3	4.3
Freq. (MHz)	209.0	208.5	209.0	208.5
Limit (dB)	14.8	14.8	14.8	14.8

N/A	MAIN	SR	MAIN	SR
Worst Pair	3.6-4.5	1.2-3.6	3.6-4.5	1.2-3.6
ACR-N (dB)	4.5	4.5	7.9	10.1
Freq. (MHz)	35.5	80.8	246.0	247.0
Limit (dB)	38.4	26.8	4.6	4.5
Worst Pair	3.6	3.6	3.6	1.2
PS ACR-N (dB)	5.5	5.5	9.4	10.2
Freq. (MHz)	5.5	83.8	250.0	247.5
Limit (dB)	55.5	23.7	1.6	1.9

PASS	MAIN	SR	MAIN	SR
Worst Pair	3.6	3.6	4.5	3.6
RL (dB)	6.6	4.3	8.7	8.8
Freq. (MHz)	3.8	3.8	247.5	234.5
Limit (dB)	21.0	21.0	10.1	10.3

Compliant Network Standards:
10BASE-T
100BASE-T
ATM-25
100VG-AnyLan
TR-16 Passive

100BASE-T4
5GBASE-T
ATM-155
TR-16 Active




LinkWare™ PC Version 10.7



FLUKE
networks

Electrical Characteristics

PoE Certification	PoE/PoE+/PoE++ 4PPoE
Maximum PoE Wattage	100W
PoE Application Compatibility	802.3af/at/bt Type 4
TIA 568-2.D Cat5e Permanent Link + PoE	CERTIFIED
Maximum Application Speed @ 295ft	2.5GBASE-T
Nominal Velocity of Propagation (NVP)	70.5
Maximum Operating Voltage	300V
1.0 - 350MHz Impedance (Ω)	100 $\pm$ 15
Maximum Operating Frequency	350MHz
1.0 - 350MHz Delay Skew (ns/100m)	$\leq$ 45
Pair-to-Ground Capacitance Unbalance (pF/km)	$\leq$ 3300
Max. Conductor DC Resistance 20°C (Ω /km)	93.8



Mechanical & Environmental Operating Parameters

Test Object	Jacket	Aging Condition (h x hrs)	100 x 168 $\geq$ 85% of
Test Material	PVC	After Tensile Strength (Mpa)	unaged $\geq$ 50% of
Before- Tensile Strength (Mpa)	$\geq$ 13.8	Aging Condition - Elongation (%)	unaged
Aging- Elongation (%)	$\geq$ 100	Cold Bend (-20 $\pm$ 2°C x 4hrs)	No Crack
Min. Bend Radius	2.0cm/0.75in	Operating & Storage Temp.	-40°C to 75°C -40°F to 167°F
Max. Installation Tension	110N/25lb-ft	Installation Temp.	-20°C to 75°C -4°F to 167°F

